

# GQ35L



Laser pointer  
Laser Ranging



1920X1080  
HD visible light



640X512  
Ultra-clear detector



IP67 level  
Professional  
protection



**Hikvision Super Starlight Technology**  
Integrated with the thermal imaging screen in equal proportions, it will be wonderful in 24h  
See the details in the stars



# King Yan

## Three Lights in One, Insight Opportunities

- 1600m ultra-distance detection
- Super starlight visible eye
- Precision ranging laser
- IP67 waterproof and anti-drop
- One-handed operation



Special ticket  
can be issued

Nationwide warranty

Model: GQ35L



### Laser Ranging

The distance is clearly visible



Visible light + thermal imaging  
Double light fusion



Haikang Super Starlight  
Image Technology  
The night is still clear



Ultra-distance detection  
Detection distance 1600m+

# Six modes for you to choose

## Meet all your needs



# Product Parameters

## Three Mode In One



Model		GQ35L	GQ25L	GH19L
Thermal Imagery	Sensor Type	Uncooled VOx Detectors		
	Resolution	640x512		384x288
	Cell size	12 μm		
	Wavelength	8-14 μm		
	NETD	<45mk(@25°C,F#=1.0)		
	Lens Focal Length	35mm	25mm	19mm
	Detection Distance	1600m	1250m	950m
	Field of view	10.97° × 8.82°	10.97° × 8.78°	11.83° × 8.88°
	Max.aperture value	F1.0		
Frame Rate	50 fps			
Focusing	Manual Focusing			
Visible Light	Imaging Resolution	1920x1080		
	Display Resolution	1024x768		
Image Display	Display Screen	OLED		
	Image Mode	White Hot,Black Hot,Red Hot,Fusion,Visible Mode,Dual-light Fusion		
	Brightness/Contrast	1~5 gears adjustable		
	Scene Mode	Recognition mode, jungle mode		
	Digital Zoom	1x,2x,4x,8x		
System Functions	Diopter Adjustment	Support		
	WIFI	Support		
	Interface	Support Type-C		
	Snapshot/Video	Support		
	Wheel button	Support		
Laser Pointing/Ranging	Support			
System Parameters	Power supply	Removable battery		
	Storage	Support, built-in EMMC v5.1 interface high-speed storage (maximum 16GB)		
	Battery Life	4.5h		
	Operating Temperature	-30-55°C		
	Protection Grade	IP67		
	weight	<510g		
size	≤87 × 73.3 × 167.8mm	≤87.2 × 73.3 × 161.5mm		